


Server IP20 800x1000 - Free standing



Description

The Server Series has been designed to use in Data Centers of any size. Thanks to its robustness, this cabinet can support considerable loads to install servers, uninterruptible power supplies and devices of any manufacturer.

Technical features

The modular structure, is made of four (4), load-bearing, steel sheet, 2.0 mm-thick and rounded-corner profiles, to guarantee exceptional strength. Assembly and disassembly of the complete structure is straightforward and quick. The Rack can be supplied either fully assembled or in flat-pack packaging. Racks of this Series are available with tempered glass front door fitted with a swivel handle lock with key. Side and rear panels are removable and fitted with a quarter-turn lock. On request, they can be supplied with lock with key.


Technical Specifications

Structure	Modular and disassemblable	Levelling feet	4 pcs of M10x35 mm
Material	2.0 mm steel sheet	Cable entry	Pre-cut, base and roof (optional brush)
Static load	1000 kg	Roof ventilation	Natural or forced (up to four fans)
19" Uprights	4 pcs, C=2.00 mm, 19" as per IEC 60297-1-2	Color	Epoxy powder Black RAL 9005
Front door	With 4.0 mm glass, tempered as per EN 12150-1	Protection degree	IP20 according to EN 60529
Side panels	Removable, 1.0 mm steel sheet, with ¼ turn lock	Conformity	RoHS 2 Directive 2011/65 / EU
Rear panel	Removable, 1.0 mm steel sheet, with ¼ turn lock	Warranty	2 years


Server IP20 800x1000 - Free standing

Construction Drawing

- ① Modular and disassemblable structure
- ② Depth-adjustable 19" uprights
- ③ Glass front door with swivel handle
- ④ Removable side and rear panels
- ⑤ Cable entry from base and roof
- ⑥ Allows the installation of ventilation
- ⑦ Levelling feet



Dimensions



Versions

P/N	Description	Units	Height	Width	Depth	Color
309071-AV-PP-SZ	Server IP20 with glass door	24	1156 mm	800 mm	1000 mm	Black, RAL 9005
309073-AV-PP-SZ	Server IP20 with glass door	34	1601 mm	800 mm	1000 mm	Black, RAL 9005
309075-AV-PP-SZ	Server IP20 with glass door	42	1957 mm	800 mm	1000 mm	Black, RAL 9005
309077-AV-PP-SZ	Server IP20 with glass door	48	2224 mm	800 mm	1000 mm	Black, RAL 9005

Other dimensions and configurations are available on request.

Accessories

P/N	Description	Height	Width	Depth	Color
309342	Brush for the cable entry (2 pcs)	10.4 mm	50 mm	301 mm	Black, RAL 9005
309335	Plinth kit with sealing flanges	100 mm	800 mm	1000 mm	Black, RAL 9005