

Accessories - Power Distribution Units (PDU)

Description

PDU's are critical devices that ensure reliable distribution of power to the output sockets for low and medium-voltage equipment installed in a rack cabinet. A PDU simplifies the electrical connection of multiple devices when implementing Data Centers, Network Infrastructures, Datacomm, Audio Visual or other applications.



309139 - 309144



309140 - 309147



309145



309146

Dimensions

P/N	309139	309140	309145	309147	309146	309144
Rack unit	1U	1U	1U	0U	1U	1U
Fixing	19"	19"	19"	Vertical	19"	19"
Dimensions (W)x(D)x(H)	(19") 482.6x45x45 mm	(19") 482.6x45x45 mm	(19") 482.6x45x45 mm	(19") 728.3x45x45 mm	(19") 482.6x45x45 mm	(19") 482.6x45x45 mm
Case	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Color	Black	Black	Black	Black	Black	Black

Technical Specifications

P/N	309139	309140	309145	309147	309146	309144
Socket type	(8) Universal Schuko 45°	(6) Universal Schuko 45°	(6) Universal Schuko 45°	(12) Universal Schuko 45°	(8) IEC320 C13	(8) Universal Schuko 45°
Nominal tension	250VAC 50/60Hz	250VAC 50/60Hz	250VAC 50/60Hz	250VAC 50/60Hz	250VAC 50/60Hz	250VAC 50/60Hz
Rated current	16A	16A	16A	16A	16A	16A
Plug	Schuko	Schuko	Italian	Schuko	Schuko	IEC320 C14
Power cable	H05VV-F3G x 1.5 mm 2 x 2m	H05VV-F3G x 1.5 mm 2 x 2m	H05VV-F3G x 1.5 mm 2 x 2m	H05VV-F3G x 1.5 mm 2 x 2m	H05VV-F3G x 1.5 mm 2 x 2m	H05VV-F3G x 1.5 mm 2 x 2m
Power	4000W	4000W	4000W	4000W	4000W	4000W
Switch	ON/OFF with light	Magneto-thermal	ON / OFF bright	Magneto-thermal	ON / OFF bright	ON / OFF bright
Operating temperature	-10°C to 45°C	-10°C to 45°C	-10°C to 45°C	-10°C to 45°C	-10°C to 45°C	-10°C to 45°C
Compliance	RoHS 2 2011/65/EU	RoHS 2 2011/65/EU	RoHS 2 2011/65/EU	RoHS 2 2011/65/EU	RoHS 2 2011/65/EU	RoHS 2 2011/65/EU
Compliance	CE	CE	CE	CE	CE	CE
Warranty	2 years	2 years	2 years	2 years	2 years	2 years



309139 - 309140 - 309145 - 309147 - 309146 - 309144: Network - Server - Office - Office Small - Industrial IP55 - Industrial IP65