

Accessories - Power Distribution Units (PDU)

Description

PDU's are critical devices that ensure reliable distribution of power to the output sockets for low and medium-voltage equipment installed in a rack cabinet. A PDU simplifies the electrical connection of multiple devices when implementing Data Centers, Network Infrastructures, Datacomm, Audio Visual or other applications.



309139 - 309144



309140 - 309147



309145



309146

Dimensions

| P/N | 309139 | 309140 | 309145 | 309147 | 309146 | 309144 |
|------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Rack unit | 1U | 1U | 1U | 0U | 1U | 1U |
| Fixing | 19" | 19" | 19" | Vertical | 19" | 19" |
| Dimensions (W)x(D)x(H) | (19") 482.6x45x45 mm | (19") 482.6x45x45 mm | (19") 482.6x45x45 mm | (19") 728.3x45x45 mm | (19") 482.6x45x45 mm | (19") 482.6x45x45 mm |
| Case | Aluminium | Aluminium | Aluminium | Aluminium | Aluminium | Aluminium |
| Color | Black | Black | Black | Black | Black | Black |

Technical Specifications

| P/N | 309139 | 309140 | 309145 | 309147 | 309146 | 309144 |
|-----------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Socket type | (8) Universal Schuko 45° | (6) Universal Schuko 45° | (6) Universal Schuko 45° | (12) Universal Schuko 45° | (8) IEC320 C13 | (8) Universal Schuko 45° |
| Nominal tension | 250VAC 50/60Hz | 250VAC 50/60Hz | 250VAC 50/60Hz | 250VAC 50/60Hz | 250VAC 50/60Hz | 250VAC 50/60Hz |
| Rated current | 16A | 16A | 16A | 16A | 16A | 16A |
| Plug | Schuko | Schuko | Italian | Schuko | Schuko | IEC320 C14 |
| Power cable | H05VV-F3G x 1.5 mm 2 x 2m | H05VV-F3G x 1.5 mm 2 x 2m | H05VV-F3G x 1.5 mm 2 x 2m | H05VV-F3G x 1.5 mm 2 x 2m | H05VV-F3G x 1.5 mm 2 x 2m | H05VV-F3G x 1.5 mm 2 x 2m |
| Power | 4000W | 4000W | 4000W | 4000W | 4000W | 4000W |
| Switch | ON/OFF with light | Magneto-thermal | ON / OFF bright | Magneto-thermal | ON / OFF bright | ON / OFF bright |
| Operating temperature | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C |
| Compliance | RoHS 2 2011/65/EU | RoHS 2 2011/65/EU | RoHS 2 2011/65/EU | RoHS 2 2011/65/EU | RoHS 2 2011/65/EU | RoHS 2 2011/65/EU |
| Compliance | CE | CE | CE | CE | CE | CE |
| Warranty | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years |



309139 - 309140 - 309145 - 309147 - 309146 - 309144: Network - Server - Office - Office Small - Industrial IP55 - Industrial IP65